


## RAD-HARD HEX BUFFER/CONVERTER (INVERTER)

- HIGH SPEED:  
 $t_{PD} = 8ns$  (TYP.) at  $V_{CC}=6V$
- LOW POWER DISSIPATION:  
 $I_{CC} = 1\mu A$  (MAX.) at  $T_A=25^\circ C$
- HIGH NOISE IMMUNITY:  
 $V_{NIH} = V_{NIL} = 28\% V_{CC}$  (MIN.)
- SYMMETRICAL OUTPUT IMPEDANCE:  
 $|I_{OH}| = I_{OL} = 6mA$  (MIN)
- BALANCED PROPAGATION DELAYS:  
 $t_{PLH} \cong t_{PHL}$
- WIDE OPERATING VOLTAGE RANGE:  
 $V_{CC}$  (OPR) = 2V to 6V
- PIN AND FUNCTION COMPATIBLE WITH 54 SERIES 4049
- SPACE GRADE-1: ESA SCC QUALIFIED
- 50 krad QUALIFIED, 100 krad AVAILABLE ON REQUEST
- NO SEL UNDER HIGH LET HEAVY IONS IRRADIATION
- DEVICE FULLY COMPLIANT WITH SCC-9401-037

### DESCRIPTION

The M54HC4049 is an high speed CMOS HEX BUFFER (INVERTING) fabricated with silicon gate C<sup>2</sup>MOS technology.



### ORDER CODES

| PACKAGE | FM         | EM          |
|---------|------------|-------------|
| DILC    | M54HC4049D | M54HC4049D1 |
| FPC     | M54HC4049K | M54HC4049K1 |

The internal circuit is composed of 2 stage inverters, which enables high noise immunity and a stable output.

Input protection circuits are different from those of the high speed CMOS IC's.

The  $V_{CC}$  side diodes are designed to allow logic-level conversion from high-level voltages (up to 13V) to low level voltages.

### PIN CONNECTION




Figure 1: IEC Logic Symbols




Figure 2: Input And Output Equivalent Circuit




Table 1: Pin Description

| PIN N°              | SYMBOL                     | NAME AND FUNCTION       |
|---------------------|----------------------------|-------------------------|
| 2, 4, 6, 10, 12, 15 | 1 $\bar{Y}$ to 6 $\bar{Y}$ | Data Outputs            |
| 3, 5, 7, 9, 11, 14  | 1A to 6A                   | Data Inputs             |
| 13, 16              | NC                         | Not Connected           |
| 8                   | GND                        | Ground (0V)             |
| 1                   | V <sub>CC</sub>            | Positive Supply Voltage |

Table 2: Truth Table

| INPUT | OUTPUT      |
|-------|-------------|
| nA    | n $\bar{Y}$ |
| L     | H           |
| H     | L           |

Table 3: Absolute Maximum Ratings

| Symbol                              | Parameter                            | Value                         | Unit |
|-------------------------------------|--------------------------------------|-------------------------------|------|
| V <sub>CC</sub>                     | Supply Voltage                       | -0.5 to +7                    | V    |
| V <sub>I</sub>                      | DC Input Voltage                     | -0.5 to 15                    | V    |
| V <sub>O</sub>                      | DC Output Voltage                    | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| I <sub>IK</sub>                     | DC Input Diode Current               | – 20                          | mA   |
| I <sub>OK</sub>                     | DC Output Diode Current              | ± 20                          | mA   |
| I <sub>O</sub>                      | DC Output Current                    | ± 25                          | mA   |
| I <sub>CC</sub> or I <sub>GND</sub> | DC V <sub>CC</sub> or Ground Current | ± 50                          | mA   |
| P <sub>D</sub>                      | Power Dissipation                    | 300                           | mW   |
| T <sub>stg</sub>                    | Storage Temperature                  | -65 to +150                   | °C   |
| T <sub>L</sub>                      | Lead Temperature (10 sec)            | 265                           | °C   |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied

Table 4: Recommended Operating Conditions

| Symbol     | Parameter                |                 | Value         | Unit |
|------------|--------------------------|-----------------|---------------|------|
| $V_{CC}$   | Supply Voltage           |                 | 2 to 6        | V    |
| $V_I$      | Input Voltage            |                 | 0 to 13       | V    |
| $V_O$      | Output Voltage           |                 | 0 to $V_{CC}$ | V    |
| $T_{op}$   | Operating Temperature    |                 | -55 to 125    | °C   |
| $t_r, t_f$ | Input Rise and Fall Time | $V_{CC} = 2.0V$ | 0 to 1000     | ns   |
|            |                          | $V_{CC} = 4.5V$ | 0 to 500      | ns   |
|            |                          | $V_{CC} = 6.0V$ | 0 to 400      | ns   |

Table 5: DC Specifications

| Symbol          | Parameter                 | Test Condition         |  | Value                 |      |                |             |            |              |      |    | Unit |
|-----------------|---------------------------|------------------------|--|-----------------------|------|----------------|-------------|------------|--------------|------|----|------|
|                 |                           | V <sub>CC</sub><br>(V) |  | T <sub>A</sub> = 25°C |      |                | -40 to 85°C |            | -55 to 125°C |      |    |      |
|                 |                           |                        |  | Min.                  | Typ. | Max.           | Min.        | Max.       | Min.         | Max. |    |      |
| V <sub>IH</sub> | High Level Input Voltage  | 2.0                    |  | 1.5                   |      |                | 1.5         |            | 1.5          |      | V  |      |
|                 |                           | 4.5                    |  | 3.15                  |      |                | 3.15        |            | 3.15         |      |    |      |
|                 |                           | 6.0                    |  | 4.2                   |      |                | 4.2         |            | 4.2          |      |    |      |
| V <sub>IL</sub> | Low Level Input Voltage   | 2.0                    |  |                       |      | 0.5            |             | 0.5        |              | 0.5  | V  |      |
|                 |                           | 4.5                    |  |                       |      | 1.35           |             | 1.35       |              | 1.35 |    |      |
|                 |                           | 6.0                    |  |                       |      | 1.8            |             | 1.8        |              | 1.8  |    |      |
| V <sub>OH</sub> | High Level Output Voltage | 2.0                    | I <sub>O</sub> =-20 μA   | 1.9                   | 2.0  |                | 1.9         |            | 1.9          |      | V  |      |
|                 |                           | 4.5                    | I <sub>O</sub> =-20 μA   | 4.4                   | 4.5  |                | 4.4         |            | 4.4          |      |    |      |
|                 |                           | 6.0                    | I <sub>O</sub> =-20 μA   | 5.9                   | 6.0  |                | 5.9         |            | 5.9          |      |    |      |
|                 |                           | 4.5                    | I <sub>O</sub> =-4.0 mA  | 4.18                  | 4.31 |                | 4.13        |            | 4.10         |      |    |      |
|                 |                           | 6.0                    | I <sub>O</sub> =-5.2 mA  | 5.68                  | 5.8  |                | 5.63        |            | 5.60         |      |    |      |
| V <sub>OL</sub> | Low Level Output Voltage  | 2.0                    | I <sub>O</sub> =20 μA  |                       | 0.0  | 0.1            |             | 0.1        |              | 0.1  | V  |      |
|                 |                           | 4.5                    | I <sub>O</sub> =20 μA  |                       | 0.0  | 0.1            |             | 0.1        |              | 0.1  |    |      |
|                 |                           | 6.0                    | I <sub>O</sub> =20 μA  |                       | 0.0  | 0.1            |             | 0.1        |              | 0.1  |    |      |
|                 |                           | 4.5                    | I <sub>O</sub> =4.0 mA   |                       | 0.17 | 0.26           |             | 0.33       |              | 0.40 |    |      |
|                 |                           | 6.0                    | I <sub>O</sub> =5.2 mA   |                       | 0.18 | 0.26           |             | 0.33       |              | 0.40 |    |      |
| I <sub>I</sub>  | Input Leakage Current     | 6.0                    | V <sub>I</sub> = V <sub>CC</sub> or GND<br>V <sub>I</sub> = 13 V |                       |      | ± 0.1<br>± 0.5 |             | ± 1<br>± 5 |              | ± 1  | μA |      |
| I <sub>CC</sub> | Quiescent Supply Current  | 6.0                    | V <sub>I</sub> = V <sub>CC</sub> or GND                          |                       |      | 1              |             | 10         |              | 20   | μA |      |

Table 6: AC Electrical Characteristics ( $C_L = 50\text{ pF}$ , Input  $t_r = t_f = 6\text{ ns}$ )


| Symbol                            | Parameter              | Test Condition         |                        |  | Value                 |      |      |             |      |              | Unit |      |
|-----------------------------------|------------------------|------------------------|------------------------|--|-----------------------|------|------|-------------|------|--------------|------|------|
|                                   |                        | V <sub>CC</sub><br>(V) | C <sub>L</sub><br>(pF) |  | T <sub>A</sub> = 25°C |      |      | -40 to 85°C |      | -55 to 125°C |      |      |
|                                   |                        |                        |                        |  | Min.                  | Typ. | Max. | Min.        | Max. | Min.         |      | Max. |
| t <sub>TLH</sub> t <sub>THL</sub> | Output Transition Time | 2.0                    | 50                     |  |                       | 25   | 60   |             | 75   |              | 90   | ns   |
|                                   |                        | 4.5                    |                        |  |                       | 7    | 12   |             | 15   |              | 18   |      |
|                                   |                        | 6.0                    |                        |  |                       | 6    | 10   |             | 13   |              | 15   |      |
| t <sub>PLH</sub> t <sub>PHL</sub> | Propagation Delay Time | 2.0                    | 50                     |  |                       | 30   | 75   |             | 95   |              | 115  | ns   |
|                                   |                        | 4.5                    |                        |  |                       | 9    | 15   |             | 19   |              | 23   |      |
|                                   |                        | 6.0                    |                        |  |                       | 8    | 13   |             | 16   |              | 20   |      |
|                                   |                        | 2.0                    | 150                    |  |                       | 45   | 100  |             | 125  |              | 150  |      |
|                                   |                        | 4.5                    |                        |  |                       | 14   | 20   |             | 25   |              | 30   |      |
|                                   |                        | 6.0                    |                        |  |                       | 12   | 17   |             | 21   |              | 26   |      |

Table 7: Capacitive Characteristics


| Symbol          | Parameter                              | Test Condition         |  | Value                 |      |      |             |      |              | Unit |      |
|-----------------|--|------------------------|--|-----------------------|------|------|-------------|------|--------------|------|------|
|                 |  | V <sub>CC</sub><br>(V) |  | T <sub>A</sub> = 25°C |      |      | -40 to 85°C |      | -55 to 125°C |      |      |
|                 |  |                        |  | Min.                  | Typ. | Max. | Min.        | Max. | Min.         |      | Max. |
| C <sub>IN</sub> | Input Capacitance                      | 5.0                    |  |                       | 5    | 10   |             | 10   |              | 10   | pF   |
| C <sub>PD</sub> | Power Dissipation Capacitance (note 1) | 5.0                    |  |                       | 26   |      |             |      |              |      | pF   |

1)  $C_{PD}$  is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average operating current can be obtained by the following equation.  $I_{CC(opr)} = C_{PD} \times V_{CC} \times f_{IN} + I_{CC}/6$  (per gate)

Figure 3: Test Circuit




$C_L = 50\text{ pF}$  or equivalent (includes jig and probe capacitance)  
 $R_T = Z_{OUT}$  of pulse generator (typically  $50\Omega$ )

Figure 4: Waveform - Propagation Delay Times ( $f=1\text{MHz}$ ; 50% duty cycle)

S-10441

DILC-16 MECHANICAL DATA


| DIM. | mm.   |       |       | inch  |       |       |
|------|-------|-------|-------|-------|-------|-------|
|      | MIN.  | TYP   | MAX.  | MIN.  | TYP.  | MAX.  |
| A    | 2.1   |       | 2.71  | 0.083 |       | 0.107 |
| a1   | 3.00  |       | 3.70  | 0.118 |       | 0.146 |
| a2   | 0.63  | 0.88  | 1.14  | 0.025 | 0.035 | 0.045 |
| B    | 1.82  |       | 2.39  | 0.072 |       | 0.094 |
| b    | 0.40  | 0.45  | 0.50  | 0.016 | 0.018 | 0.020 |
| b1   | 0.20  | 0.254 | 0.30  | 0.008 | 0.010 | 0.012 |
| D    | 20.06 | 20.32 | 20.58 | 0.790 | 0.800 | 0.810 |
| E    | 7.36  | 7.62  | 7.87  | 0.290 | 0.300 | 0.310 |
| e    |       | 2.54  |       |       | 0.100 |       |
| e1   | 17.65 | 17.78 | 17.90 | 0.695 | 0.700 | 0.705 |
| e2   | 7.62  | 7.87  | 8.12  | 0.300 | 0.310 | 0.320 |
| F    | 7.29  | 7.49  | 7.70  | 0.287 | 0.295 | 0.303 |
| I    |       |       | 3.83  |       |       | 0.151 |
| K    | 10.90 |       | 12.1  | 0.429 |       | 0.476 |
| L    | 1.14  |       | 1.5   | 0.045 |       | 0.059 |



0056437F

FPC-16 MECHANICAL DATA

| DIM. | mm.   |       |       | inch  |       |       |
|------|-------|-------|-------|-------|-------|-------|
|      | MIN.  | TYP   | MAX.  | MIN.  | TYP.  | MAX.  |
| A    | 6.75  | 6.91  | 7.06  | 0.266 | 0.272 | 0.278 |
| B    | 9.76  | 9.94  | 10.14 | 0.384 | 0.392 | 0.399 |
| C    | 1.49  |       | 1.95  | 0.059 |       | 0.077 |
| D    | 0.102 | 0.127 | 0.152 | 0.004 | 0.005 | 0.006 |
| E    | 8.76  | 8.89  | 9.01  | 0.345 | 0.350 | 0.355 |
| F    |       | 1.27  |       |       | 0.050 |       |
| G    | 0.38  | 0.43  | 0.48  | 0.015 | 0.017 | 0.019 |
| H    | 6.0   |       |       | 0.237 |       |       |
| L    | 18.75 |       | 22.0  | 0.738 |       | 0.867 |
| M    | 0.33  | 0.38  | 0.43  | 0.013 | 0.015 | 0.017 |
| N    |       | 4.31  |       |       | 0.170 |       |



0016030E

**Table 8: Revision History**

| Date        | Revision | Description of Changes |
|-------------|----------|------------------------|
| 14-May-2004 | 1        | First Release          |



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics  
All other names are the property of their respective owners

© 2004 STMicroelectronics - All Rights Reserved  
STMicroelectronics GROUP OF COMPANIES

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.  
<http://www.st.com>