


Tornillo estándar
Cabeza cuadrada



Diámetro nominal	D Diámetro de cuerpo máximo (básica)	F Distancia entre planos		G Distancia entre esquinas		H Altura			R radio de enlace máximo
		Máxima	Mínima	Máxima	Mínima	Nominal	Máxima	Mínima	
Dimensiones en milímetros									
6.3	7.1	9.5	9.2	15.5	12.7	4.4	4.8	4.0	0.8
7.9	8.7	12.7	12.3	18.0	16.9	5.2	5.6	4.7	0.8
9.5	10.4	14.3	13.8	20.2	19.0	6.3	6.8	5.9	0.8
11.1	11.8	15.9	15.3	22.5	21.0	7.5	8.0	7.1	0.8
12.7	13.5	19.1	18.4	27.0	25.3	8.3	8.8	7.8	0.8
15.9	17.1	23.8	23.0	33.7	31.6	10.7	11.3	10.2	1.6
19.0	20.3	28.6	27.6	40.4	38.0	12.7	13.3	12.1	1.6
22.2	23.8	33.3	32.2	47.1	44.2	15.1	15.8	14.4	1.6
25.4	27.0	38.1	36.8	53.9	50.6	16.7	17.4	16.0	1.6
28.6	30.2	42.9	41.4	60.6	56.9	19.1	19.8	18.3	3.2
31.8	33.3	47.6	46.0	67.4	63.2	21.4	22.3	20.6	3.2
Equivalencia en pulgadas									
1/4	.280	.3750	.363	.530	.498	11/64	.188	.156	.031
5/16	.342	.5000	.484	.707	.665	13/64	.220	.186	.031
3/8	.405	.5625	.544	.795	.747	1/4	.268	.232	.031
7/16	.468	.6250	.603	.884	.828	19/64	.316	.278	.031
1/2	.530	.7500	.725	1.061	.995	21/64	.348	.308	.031
5/8	.675	.9375	.906	1.326	1.244	27/64	.444	.400	.062
3/4	.800	1.1250	1.088	1.591	1.494	1/2	.524	.476	.062
7/8	.938	1.3125	1.269	1.856	1.742	19/32	.620	.568	.062
1	1.063	1.5000	1.450	2.121	1.991	21/32	.684	.628	.062
1 1/8	1.188	1.6875	1.631	2.386	2.239	3/4	.780	.720	.125
1 1/4	1.313	1.8750	1.813	2.652	2.489	27/32	.876	.812	.125